



STANDARD

5228 A

Cable type : **5228 A**
Reference : **EC5-50-A**

Cable with standard UV resistant PE jacket, halogen free according to IEC 60754

FLAME RETARDANT

HLFR

Cable type : **5228A-HLFR**
Reference : **EC5-50A-FR**

Cable with UV resistant, halogen free, low smoke, flame retardant jacket according to IEC 60754-2, IEC 60332-1-2, IEC 60332-3 Cat. C and IEC 61034-1+2

CHARACTERISTICS

Construction

• Inner conductor	
Material	smooth copper tube
Diameter (mm)	9.3
• Dielectric	
Material	gas-injected cellular polyethylene
Diameter (mm)	23.5
• Outer conductor	
Material	corrugated copper tube
Diameter (mm)	25.0
• Jacket	
Material	black polyethylene
Thickness (mm)	1.4
Diameter (mm)	28.0

Mechanical

• Minimum bending radius	
a) single bending (cm)	10
b) 15 repeated bends (cm)	25
• Maximum pulling strength (daN)	150
• Recommended temperature range	
- Storage	-70 to +85°C
- Installation	-40 to +60°C
- Operation	-55 to +85°C
• Maximum length per hoisting grip (m)	70
• Maximum hanger spacing	1.2
• Flat Plate Crush resistance (kg/mm)	1.4
• Bending moment (Nm)	11.6
• Weight (kg/km)	496

[1] a = 0.1107
b = 0.000333
 $\alpha(f) = a \cdot \sqrt{f} + b \cdot f$ [dB/100m]

Electrical

• Characteristic impedance (Ω)	50 ±1
• Nominal capacity (pF/m)	75
• Relative propagation velocity (%)	89
• Inductance (μH/m)	0.187
• DC-resistance at 20°C	
- inner conductor (Ω/km)	1.34
- outer conductor (Ω/km)	1.0
• RF peak voltage (kV)	2.9
• RF peak power (kW)	86
• Cut-off-frequency (GHz)	5.1
• Insulation resistance (MΩ.km)	>>5000

• Attenuation [1] and power rating

Frequency (MHz)	Attenuation at 20°C(*) (dB/100m)	Mean power rating(**) (kW)
10	0.35	25.46
20	0.50	17.93
30	0.62	14.60
80	1.02	8.85
100	1.14	7.89
150	1.41	6.40
200	1.63	5.51
300	2.02	4.46
400	2.35	3.83
450	2.50	3.60
500	2.64	3.41
600	2.91	3.09
700	3.16	2.85
800	3.40	2.65
894	3.61	2.49
960	3.75	2.40
1000	3.83	2.35
1500	4.79	1.88
1700	5.13	1.75
1800	5.30	1.70
1880	5.43	1.66
2000	5.62	1.60
2170	5.88	1.53
2200	5.92	1.52
2300	6.07	1.48
2400	6.22	1.45
2500	6.37	1.41
3000	7.06	1.27
4000	8.33	1.08
6000	-	-

(*) nominal values

(**) Ambient temperature = 40°C; Temperature of inner conductor = 100°C; VSWR = 1.0; no solar loading