



NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
 1. BRASS PER QQ-B-626
 2. BRASS PER QQ-B-613
 3. NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 4. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 5. JIS H 3250, C 2700

10	COVER	NOTE 1	NOTE 3	1	B1112A4-10
9	FERRULE	NOTE 5	NOTE 3	1	FR-124/109X158
8	WASHER	NOTE 2	NOTE 3	1	WS-128/9X08
7	RING	DELTRIN	NATURAL	1	T50000-6-A
6	RETAINER RING	NOTE 1	NOTE 3	1	B50000-5
5	GASKET	RUBBER	RED	1	GS-105/8X15
4	CONTACT PIN	NOTE 1	NOTE 4	1	B1112A4-4-38/29
3	INSULATOR	DELTRIN	NATURAL	1	B1112A4-3-50
2	HOUSING WITH BODY	NOTE 1	NOTE 3	1	B1112A4-25-93/74
1	SHELL	NOTE 1	NOTE 3	1	T50000-1-B

DIMENSIONS ARE IN MILLIMETERS		PART NO.	
UNLESS OTHERWISE SPECIFIED TOLERANCES		APPROVED	DATE
0.5-6 = ±0.2	6-30 = ±0.4	<i>[Signature]</i>	06-20-01'
30-120 = ±0.6	120-315 = ±1	CHECKED	DATE
315-1000 = ±1.6	1000-2000 = ±2.4	Robin	06-20-01'
		DRAWN	DATE
		Robin	06-20-01'

Amphenol-Kai Jack ShenZhen China	
TITLE	TNC R/A CRIMP PLUG (FOR BELDEN 9913, 9914)
DRAWING NO.	T1112A4-ND3G-9913-50
FILE NO.	F:\DWG\T\1112A4\9913-50\ND3GSZ