



**SALES**

RECOMMENDED  
CABLE STRIPPING DIM'S  
(建議剝線尺寸)

ISSUED  
2003. 4. 18  
P. B. D.

1. CONTACT PIN TO SOLDER

ISS	ZONE	DESCRIPTION\PER REQUEST\DATE				
14		NUT	NOTE 1	NOTE 3	1	B5291-14
13		HEX NUT	NOTE 1	NOTE 3	1	HN00AAF14A
12		WASHER	NOTE 2	NOTE 3	1	WS-85/65X05
11		GASKET.	SILICONE	RED	1	GS-8/53X5
10		TOP HAT	NOTE 1	NOTE 5	1	B1141E1-11-37/32
9		WASHER	NOTE 2	NOTE 3	1	WS-128/9X08
8		RING	DELTRIN	NATURAL	1	T50000-6-A
7		RETAINER RING	NOTE 1	NOTE 3	1	B50000-5
6		GASKET	RUBBER	RED	1	GS-105/8X15
5		CONTACT PIN	NOTE 1	NOTE 4	1	B5091-6-50
4		INSULATOR	DELTRIN	NATURAL	1	B50002-3-50
3		BODY	NOTE 1	NOTE 3	1	B5291-3-11/32
2		HOUSING	NOTE 1	NOTE 3	1	B5091-2
1		SHELL	NOTE 1	NOTE 3	1	T50000-1-B
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.	

NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)  
 1. BRASS PER QQ-B-626  
 2. BRASS PER QQ-B-613  
 3. NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE  
 4. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE  
 5. SILVER PL. 80 MIN. THICK OVER COPPER STRIKE

DIMENSIONS ARE IN MILLIMETERS			PART NO.
UNLESS OTHERWISE SPECIFIED TOLERANCES			APPROVED
0.5-6 = ±0.2			DATE 02-20-03'
6-30 = ±0.4			CHECKED
30-120 = ±0.6			DATE 02-20-03'
120-315 = ±1			DRAWN
315-1000 = ±1.6			DATE 02-20-03'
1000-2000 = ±2.4			FILE NO. F:\DWG\T\1142E1\58U-50\ND3G

<b>Amphenol</b>	
Danbury,CT,USA-Tainan,Taiwan-Shenzhen,China	
TITLE TNC R/A CLAMP PLUG (FOR RG-58C/U, 58/U, 142A/U, 223/U)	
DRAWING NO. T1142E1-ND3G-58U-50	
ITEM NO. 021142AAN58ND5F	

7/20 DR 17974 B